



Printed Pages : 4

TCE – 605

(Following Paper ID and Roll No. to be filled in your Answer Book)

**PAPER ID : 0061**

Roll No.

### B. Tech.

(SEM. VI) EXAMINATION, 2007

### EARTHQUAKE RESISTANT DESIGN OF BUILDING

Time : 3 Hours]

[Total Marks : 100

- Note :**
- (i) Attempt **all** questions.
  - (ii) All questions carry equal marks.
  - (iii) Use of code IS : 1893 is permitted.
  - (iv) Assume any data suitable, if missing.

**1** Attempt any **four** parts of the following : **5×4=20**

- a) What do you understand by earthquake?  
Explain in sufficient details. Also explain the various types of waves generated due to earthquakes.
- b) Explain the following terms :
  - i) Hypocentre
  - ii) Epicentre.
- c) What do you mean by degree of freedom?  
Explain.
- d) Explain various types of vibrations.
- e) The standard torsion seismograph records trace amplitude 8.9 mm long in N-S direction and 6.5 mm long in E-W direction. The distance to the epicentre is estimated as 112 km. The

V-0061]

1

[Contd...

station correction is + 0.2. Determine the magnitude of earthquake. The distance correction for 112 km is 3.1

- f) What do you understand by intensity and magnitude of the earthquake?

**2** Attempt any **two** parts of the following : **10×2=20**

- a) Write down the equation for dynamic equilibrium for a single degree of freedom system. Solve this equation for undamped free vibration.
- b) Derive the equation for single degree of freedom system for a damped system. Hence draw the curve for displacement versus time for an overdamped system.
- c) A steel portal frame is subjected to free vibrations by giving an initial displacement without velocity. Taking the damping as 47 of critical find the characteristics of the motion. The total mass of 40 tonnes is lumped at roof level and the column which are 10m high and 16 m apart, can be taken as weightless. Take  $E=2.1 \times 10^{11} \text{ N/m}^2$  and the moment of inertia of each column as  $0.0008 \text{ M}^4$ .


**3** Attempt any **two** parts of the following : **10×2=20**

- a) Describe the Holzer's numerical technique for determining natural periods of vibration for multi degree freedom system.
- b) Consider the three degree of freedom system shown in **fig.1**. Obtain the possible modes of vibration using either stiffness or flexibility approach.

V-0061]


2

[Contd...



**Fig. 1**

- c) Describe the Rayleigh's method for the determination of frequency in the fundamental mode of vibrations.
- 4 Attempt any **one** part of the following : **20×1 = 20**
- a) A four storey RC building is shown in **fig.2**. The height between floors is 3m and total height of building is 12m. The dead load and normal live loads are lumped at respective floors. The soil below the foundation is assumed to be hard rock. Assume the building to be used as a hospital. Determine the total base shear and distribute the base shear along the height of the building. Let the building be located in zone IV.



**Fig. 2**

V-0061]

3

[Contd...

- b)
  - i) What do you mean by infill walls? How are they useful in making the structure earthquake resistant? Explain various modes / mechanism for failure of infilled frame.
  - ii) Explain the analysis of infill wall using equivalent diagonal strut for infill with and without openings.

**5** Attempt any **two** parts of the following : **10×2=20**

- a) Explain the recommendations of IS code for detailing of RC beams for ductility.
  - b) A column in a multistorey R.C building is subjected to an axial force of 2500 kN and bending moment of 650 kN-M under gravity and earthquake loads. Define the column section for ductility. Use M20 concrete and Fe 415 grade steel.
  - c) Explain the method for determination of lateral loads in masonry buildings.
-