



Printed Pages : 3

AR-603

(Following Paper ID and Roll No. to be filled in your Answer Book)

**PAPER ID : 8550**

Roll No.

--	--	--	--	--	--	--	--	--	--

**B. Arch.**

**(SEM. VI) EXAMINATION, 2006-07  
ARCHITECTURAL STRUCTURES - VI**

*Time : 3 Hours]*

*[Total Marks : 50*

- Note :**
- (1) *Attempt all questions.*
  - (2) *In case of numerical problems assume suitable data wherever not provided.*
  - (3) *Use of IS-456 2000 is permitted*
  - (4) *Be precise in your answer.*

1. Attempt any **three** parts of the following : **4×3=12**
  - (a) State how cement sets and gains its strength. Why water is essential for setting of cement?
  - (b) Derive expression for the position of neutral axis and moment of resistance of balanced rectangular section.
  - (c) What is the difference between anchorage Bond and Flexural Bond?
  - (d) Explain application of Elastic Theory for Beams.

V-8550]

1

[Contd...

2. Attempt any **three** parts of the following : **4×3=12**

- (a) Explain stress-strain relationship for concrete with Neat sketches.
- (b) The cross section of a single reinforced concrete beam is 300 mm wide and 400 mm deep, The reinforcement bars consists of 4-16 mm diameter. If the stresses in concrete and steel do not exceed  $5 \text{ N/mm}^2$  and  $140 \text{ N/mm}^2$ . Determine the moment of resistance of the section.
- (c) Explain curtailment of Tension reinforcement in flexural members.
- (d) What do you understand by Bar Bending Schedule ?

3. Attempt **two** parts of the following :

Part A is compulsory.

- (a) Design a rectangular beam simply supported **8**  
over a clear span of 6 meter. If superimposed  
load is 30 kN/M and support width is 50 cm.  
each. Use M-20 concrete and Tor steel. Use  
limit state method.
- (b) What is stability requirement of a retaining **4**  
wall?
- (c) Explain arrangement of Transverse **4**  
Reinforcement for Axially loaded columns.

V-8550]

2

[Contd...

4. Attempt any **one** part of the following : **14×1=14**

- (a) Design a R.C. Slab for a room  $4\text{m} \times 5\text{m}$  from inside. The slab carries a live load of  $2000\text{ N/M}^2$  and is finished with 20 mm. thick granolithic topping. Take  $\sigma_{cbc} = 5\text{ N/mm}^2$ ,  $\sigma_{st} = 140\text{ N/mm}^2$   $m=19$ . The slab is simply supported at all four edges, with corner free to left.
- (b) A 4 meter high column held in position ends and restrained against rotation at one end. Its diameter is restricted to 40 cm. Calculate the reinforcement if it is required to carry a factored axial load of 1500 kN use M-20 concrete and Fc 250 grade steel.
-